

# Reclaimed

---



*Inspired By Nature,  
Made Possible By...*

**CANCOS**  
TILE & STONE



DOMREAG1224



| 12x24 |

DOMREAGMOS3HEX



| 3" Hexagon Mosaic |

DOMREAGMOSINT



| Intermix Mosaic |

DOMREAG848



| 8x48 |





DOMREBI1224



| 12x24 |

DOMREBIMOS3HEX



| 3" Hexagon Mosaic |

DOMREBIMOSINT



| Intermix Mosaic |

DOMREBI848



| 8x48 |



DOMREFU1224



| 12x24 |

DOMREFUMOS3HEX



| 3" Hexagon Mosaic |

DOMREFUMOSINT



| Intermix Mosaic |

DOMREFU848



| 8x48 |





DOMREQU1224



| 12x24 |

DOMREQUMOS3HEX



| 3" Hexagon Mosaic |

DOMREQUMOSINT



| Intermix Mosaic |

DOMREQU848



| 8x48 |



# Shade Variations

AGATA



BIANCO



QUARZO




FUMEE





# Suggested Applications



# Installation Suggestions

Plank Installation\*  Modular Setting  Joint Size **2mm**

*\*Install the offset the width of the plank. For professional installation, the use of leveling spacers for all plank and rectangular (ie. 12x24) format tiles is recommended.*

EDGE:  Straight/Pressed  Rustic  Rectified

FINISH:  Matte  Polished  Structured  
 Honed  Semi-Polished  Other

# Porcelain Type

through-body  color-bodied  glazed  unglazed  double-loaded  other \_\_\_\_\_

# Shade Variation

V1 Uniform Appearance  V2 Slight Variation  V3 Moderate Variation  V4 Substantial Variation

THICKNESS: **10mm** # OF FACES: **54**

# Slip Resistance

DCOF	Values	Applications
<b>.57</b>	0.42	Recommended Standard DCOF value for wet/dry commercial flooring
	0.65	Recommended Standard DCOF value for ADA Ramps

DIN 51130 \*R9: Industry Standard/ADA Requirements \*\*R11: Recommended For Exteriors

R9\* (3-10°)  R10 (10-19°)  R11\*\* (19-27°)  
 R12 (27-35°)  R13 (>35°)

ASTM C-1028  
ANSI A137.1  
DIN 51097/51130

DIN 51097

Class	Typical Applications	Critical Angle
<input type="checkbox"/> A	Barefoot, but mainly dry aisles and walkways, dry changing areas	≥12°
<input checked="" type="checkbox"/> B	Shower rooms, pool surrounds, wet changing areas, disinfectant spray areas (plus all Class A areas)	≥18°
<input type="checkbox"/> C	Areas constantly under water, e.g. steps into pools, foot baths, included pool surrounds, jacuzzis (plus all Class A&B areas)	≥24°

# Scratch Resistance

MINERAL	
1. Talc (Talc)	6. Microline (Glass, Glazed Tile)
2. Gypsum (Fingernail)	7. Quartz (Unglazed Porcelain)
3. Calcite (Penny)	8. Topaz (Granite)
4. Fluorite (Some Marbles)	9. Corundum (Ruby)
5. Apatite (Knife Blade)	10. Diamond (Diamond)

Industry standard ≤175mm<sup>2</sup>

MOH'S SCALE  
UNI EN ISO  
10545.6

**8**

# Wear Resistance

PEI RATING  
UNI EN ISO  
10545.7

- Class 1: Walls only
  - Class 2: Residential floors w/minimal abrasive traffic
  - Class 3: Residential interiors/light commercial traffic
  - Class 4: Medium commercial applications
  - Class 5: All commercial applications/heavy traffic
- \*Wear can vary greatly. please consult with a professional.*

# Stain Resistance

- 5: Removed after 5 minutes (hot water running)
- 4: Removed by manual cleaning (weak detergent)
- 3: Removed by mechanical cleaning (strong detergent)
- 2: Removed by immersion (24 hrs in suitable solvent)
- 1: Stain not removed

ASTM C1378-04  
UNI EN ISO  
10545.14

**5**

# Water Absorption

ASTM C-373  
UNI EN ISO  
10545.3

Absorbs 0-.5%  Absorbs .5-3%  Absorbs 3-7%  Absorbs 7% +

Impervious Interior/Exterior Frost Resistant  
 Vitreous Interior/Exterior Frost Resistant  
 Semi-Vitreous Indoor Use Only  
 Non-Vitreous Indoor Use Only

# Breaking Strength

Industry standard should be greater than  
250 lbs  
or  
50 N/MM<sup>2</sup>

ASTM C648  
UNI EN ISO  
10545.4

**PASS**

# Facial Dimension

ASTM c499-09  
UNI EN ISO  
10545.02

	Standard	Tolerance	Result
flatness	±5mm	±.5%	<b>PASS</b>
thickness	±6mm	±.5%	<b>PASS</b>
straightness	±4.5mm	±.5%	<b>PASS</b>
squareness	±5.4mm	±.6%	<b>PASS</b>
sides L/W	±1.1mm ±4.5mm	±.5%	<b>PASS</b>

# Chemical Resistance

ASTM C650  
UNI EN ISO  
10545.13

Allowances for:

	result
Acid	<b>PASS</b>
Bases	<b>PASS</b>
Chemicals	<b>PASS</b>

# Leed Information



REQUIREMENTS FOR COMMERCIAL INTERIORS/NEW CONSTRUCTION

Sustainable Sites	1 Point
Site selection	
SS CREDIT 1 Heat Island Effect-non roof Material with a solar reflectant index of at least 29.	<input type="checkbox"/>
Energy & Atmosphere	1 Point
EA CREDIT 4 Green Power: Products that optimize energy performance for floors and walls using thermal conductivity. BTU-FT	<input type="checkbox"/>
Indoor Environmental Quality	1 Point
Low-Emitting Materials-Flooring Systems	
IEQ CREDIT 3.1-7 Green Cleaning: Reducing occupants exposure to hazardous cleaning chemicals.	<input type="checkbox"/>
IEQ CREDIT 4.1 Low Emitting Adhesives: Products less than 65 G/L VOC	<input type="checkbox"/>
IEQ CREDIT 4.3 Low Emitting Materials: Flooring systems.	<input type="checkbox"/>

Materials & Resources	1 Point	2 Points
M&R CREDIT 2 Construction Waste Management: Recycling salvaged construction waste in to new reusable materials.	50% <input type="checkbox"/>	70% <input type="checkbox"/>
M&R CREDIT 4.1-4.2 Recycled Content: The sum of post consumer plus 1/2 of the pre consumer reps at least 10-20% of total value of materials.	10% <input type="checkbox"/>	20% <input type="checkbox"/>
M&R CREDIT 5 Regional Materials: Materials manufactured within 500 miles of the project site.	10% <input type="checkbox"/>	20% <input type="checkbox"/>
Innovation in Design		1-5 Points
ID CREDIT 1 Innovation in Design Measurable exemplary environmental performance.		<input type="checkbox"/>

Type: **Porcelain Stoneware**

Product Line: **Reclaimed**

*\*The marketing name for this product is property of Camcos Tile & Stone. This same product may be marketed under different names.\**