

Watermill



*Inspired By Nature,
Made Possible By...*

CANCOS
TILE & STONE

GLASS TILE

Ash

GLA WMAS LIN



Lineality

| mixed sizes |

GLA WMAS SMBRK



Small Brick

| 5/8 x 1 |

GLASS TILE

Cafe

GLA WMCA LIN



Lineality

| mixed sizes |

GLA WMCA SMBRK



Small Brick

| 5/8 x 1 |

GLASS TILE

Rain

GLA WMRA LIN



Lineality

| mixed sizes |

GLA WMRA SMBRK



Small Brick

| 5/8 x 1 |

GLASS TILE

Stone

GLA WMST LIN



Lineality

| mixed sizes |

GLA WMST SMBRK



Small Brick

| 5/8 x 1 |

GLA WMTR LIN



Lineality

| mixed sizes |

GLA WMTR SMBRK



Small Brick

| 5/8 x 1 |

COMMERCIAL USAGE

| | INTERIOR | | | EXTERIOR | |
|----------------------|-------------|---------------------|------------|-------------|------------|
| | RESIDENTIAL | LIGHT COMMERCIAL | COMMERCIAL | RESIDENTIAL | COMMERCIAL |
| Floors / Patios | | | | | |
| Walls / Backsplashes | X | X | X | X | X |
| Countertops | | | | | |
| Pool Decking | | | | | |
| Pool Linings | X | X | X | X | X |

Suitable in freezing and non-freezing climates when proper installation methods are followed.

INSTALLATION

| | |
|----------------------------|--------------------|
| Thickness | 1/4" |
| Grout Joint Recommendation | 1/8" Approximately |

TEST RESULTS

| | ASTM# | RESULT |
|---------------------|-------|-----------|
| Water Absorption | C373 | < 0.01 % |
| Breaking Strength | C648 | > 100 lbs |
| Scratch Hardness | MOHS | 4.0 |
| Chemical Resistance | C650 | Resistant |