

Albero 6



*Inspired By Nature,
Made Possible By...*

CANCOS
TILE AND STONE

RECTIFIED PORCELAIN STONEWARE

Fresh



DOM A6FR 636



| 6 x 36 |

DOM A6FR 1060



| 10 x 60 |

ALSO AVAILABLE IN EXTERIOR PAVERS. 16x48 / 24x24

RECTIFIED PORCELAIN STONEWARE

Natural



DOM A6NA 636



| 6 x 36 |

DOM A6NA 1060



| 10 x 60 |

ALSO AVAILABLE IN EXTERIOR PAVERS. 16x48 / 24x24



DOM A6SH 636



| 6 x 36 |

DOM A6SH 1060



| 10 x 60 |

ALSO AVAILABLE IN EXTERIOR PAVERS. 16x48 / 24x24



DOM A6SU 636



| 6 x 36 |

DOM A6SU 1060



| 10 x 60 |

ALSO AVAILABLE IN EXTERIOR PAVERS. 16x48 / 24x24

Fresh PARQUET

DOM A6FR 24



| 24 x 24 |



Natural PARQUET

DOM A6NA 24



| 24 x 24 |





Sun
PARQUET

DOM A6SU 24



| 24 x 24 |

Suggested Applications



Floor



Wall



Residential



Light Commercial



Heavy Commercial
*Wear can vary greatly. please consult with a professional.



Exterior



Pools

Installation Suggestions



Plank Installation*
*Install the offset the width of the plank. For professional installation, the use of leveling spacers for all plank and rectangular (ie. 12x24) format tiles is recommended.



Modular Setting



Joint Size

EDGE:



Straight/Pressed



Rustic



Rectified


FINISH:



Matte



Polished



Structured



Honed



Semi-Polished

Porcelain Type

☐ through-body

☒ color-bodied

☐ glazed

☒ unglazed


☐ double-loaded

☐ other

Shade Variation



☐ V1
Uniform
Appearance



☐ V2
Slight
Variation



☒ V3
Moderate
Variation



☐ V4
Substantial
Variation

THICKNESS:

9.5mm
10mm

OF FACES:

72

Slip Resistance

DCOF
.56



Values

0.42

Applications

Recommended Standard DCOF value
for wet/dry commercial flooring

Recommended Standard DCOF value
for ADA ramps

DIN 51130

*R9: Industry Standard/ADA Requirements **R11: Recommended For Exteriors

☐ R9* (3-10°)

☒ R10 (10-19°)

☐ R11** (19-27°)

☐ R12 (27-35°)

☐ R13 (>35°)

DIN 51097

Class

Typical Applications

Critical Angle

☒ A

Barefoot, but mainly dry aisles and walkways, dry changing areas

≥12°

☒ B

Shower rooms, pool surrounds, wet changing areas, disinfectant spray areas (plus all Class A areas)

≥18°

☒ C

Areas constantly under water, e.g. steps into pools, foot baths, inclined pool surrounds, jacuzzis (plus all Class A&B areas)

≥24°

ASTM C-1028
ANSI A137.1
DIN 51097/51130

Scratch Resistance

MOH'S SCALE
UNI EN ISO
10545.6

N/A

MINERAL

1. Talc (Talc)
2. Gypsum (Fingernail)
3. Calcite (Penny)
4. Fluorite (Some Marbles)
5. Apatite (Knife Blade)

6. Microline (Glass, Glazed Tile)
7. Quartz (Unglazed Porcelain)
8. Topaz (Granite)
9. Corundum (Ruby)
10. Diamond (Diamond)

Industry standard ≤175mm²

Wear Resistance

PEI RATING
UNI EN ISO
10545.7

☐ Class 1: Walls only

☐ Class 2: Residential floors w/minimal abrasive traffic

☐ Class 3: Residential interiors/light commercial traffic

☐ Class 4: Medium commercial applications

☒ Class 5: All commercial applications/heavy traffic

*Wear can vary greatly. please consult with a professional.

Stain Resistance

ASTM C1378-04
UNI EN ISO
10545.14

5

- 5: Removed after 5 minutes (hot water running)
- 4: Removed by manual cleaning (weak detergent)
- 3: Removed by mechanical cleaning (strong detergent)
- 2: Removed by immersion (24 hrs in suitable solvent)
- 1: Stain not removed

Water Absorption

ASTM C-373
UNI EN ISO
10545.3



Absorbs 0-5%



Absorbs .5-3%



Absorbs 3-7%



Absorbs 7%+

Impervious
Interior/Exterior
Frost Resistant

Vitreous
Interior/Exterior
Frost Resistant

Semi-Vitreous
Indoor Use Only

Non-Vitreous
Indoor Use Only

Breaking Strength

ASTM C648
UNI EN ISO
10545.4

PASS



Industry standard
should be greater than
250 lbs
or
50 N/MM²

Facial Dimension

ASTM C499-09
UNI EN ISO
10545.02

flatness

Standard
± 5mm

Tolerance
± .5%

Result
PASS

thickness

Standard
± 6mm

Tolerance
± .5%

Result
PASS

straightness

Standard
± 4.5mm

Tolerance
± .5%

Result
PASS

squareness

Standard
± 5.4mm

Tolerance
± .6%

Result
PASS

sides L/W

Standard
± 1.1mm
± 4.5mm

Tolerance
± .5%

Result
PASS

Chemical Resistance

ASTM C650
UNI EN ISO
10545.13



Allowances for:

result

Acid

PASS

Bases

PASS

Chemicals

PASS

Leed Information



REQUIREMENTS
FOR COMMERCIAL
INTERIORS/NEW
CONSTRUCTION

Sustainable Sites

Site selection

SS CREDIT 1

Heat Island Effect-non roof
Material with a solar reflectant index of at least 29.

1 Point

Energy & Atmosphere

EA CREDIT 4

Green Power: Products that optimize energy
performance for floors and walls using thermal
conductivity. BTU-FT

1 Point

Indoor Environmental Quality
Low-Emitting Materials-Flooring Systems

IEQ CREDIT 3.1-7

Green Cleaning: Reducing occupants exposure
to hazardous cleaning chemicals.

1 Point

IEQ CREDIT 4.1

Low Emitting Adhesives: Products less than
65 G/L VOC

IEQ CREDIT 4.3

Low Emitting Materials: Flooring systems.

Materials & Resources

M&R CREDIT 2

Construction Waste Management:
Recycling salvaged construction
waste in to new reusable materials.

1 Point

2 Points

M&R CREDIT 4.1-4.2

Recycled Content: The sum of
post consumer plus 1/2 of the
pre consumer reps at least 10-20%
of total value of materials.

10%

20%

M&R CREDIT 5

Regional Materials: Materials
manufactured within 500 miles
of the project site.

10%

20%

Innovation in Design

ID CREDIT 1

Innovation in Design

Measurable exemplary environmental performance.

1-5 Points

Type:
Porcelain Stoneware

Product Line:
Albero 6

*The marketing name for this product is property of Canco Tile & Stone.
This same product may be marketed under different names.*