

Cape

PORCELAIN
COLLECTION




CTS | Pro⁺

Cape COTTON

CTS Pro+



CTPCACO1224



-12x24-

CTPCACO24



-24x24-

CTPCACO12448



-24x48 rectified-

CTPCACOMOS22



-2x2 mosaic-

CTPCACOBN34




-3x24 bullnose-

CTS | Pro

Cape PEARL



CTPCAPE1224



-12x24-

CTPCAPEBN34



-3x24 bullnose-

CTPCAPE24



-24x24-

CTPCAPE2448



-24x48 rectified-

CTPCAPEMOS22



-2x2 mosaic-

Cape SAND

CTS | Pro+



CTPCASA1224



-12x24-

CTPCASA24



-24x24-

CTPCASA2448



-24x48 rectified-

CTPCASABN34




-3x24 bullnose-

CTPCASAMOS22



-2x2 mosaic-

Suggested Applications




Installation Suggestions



Porcelain Type



Shade Variation



Slip Resistance

DCOF	Values	Applications
0.50	0.42	Recommended Standard DCOF value for wet/dry commercial flooring
	0.65	Recommended Standard DCOF value for ADA ramps

DIN 51130 *R9: Industry Standard/ADA Requirements **R11: Recommended For Exteriors

<input type="checkbox"/> R9* (3-10°)	<input checked="" type="checkbox"/> R10 (10-19°)	<input type="checkbox"/> R11** (19-27°)
<input type="checkbox"/> R12 (27-35°)	<input type="checkbox"/> R13 (>35°)	

ASTM C-1028
ANSI A137.1
DIN 51097/51130

DIN 51097

Class	Typical Applications	Critical Angle
<input checked="" type="checkbox"/> A	Barefoot, but mainly dry aisles and walkways, dry changing areas	≥12°
<input type="checkbox"/> B	Shower rooms, pool surrounds, wet changing areas, disinfectant spray areas (plus all Class A areas)	≥18°
<input type="checkbox"/> C	Areas constantly under water, e.g. steps into pools, foot baths, included pool surrounds, jacuzzis (plus all Class A&B areas)	≥24°

Scratch Resistance

MOH'S SCALE
UNI EN ISO
10545.6

5

MINERAL	
1. Talc (Talc)	6. Microline (Glass, Glazed Tile)
2. Gypsum (Fingernail)	7. Quartz (Unglazed Porcelain)
3. Calcite (Penny)	8. Topaz (Granite)
4. Fluorite (Some Marbles)	9. Corundum (Ruby)
5. Apatite (Knife Blade)	10. Diamond (Diamond)

Industry standard ≤175mm²

Wear Resistance

PEI RATING
UNI EN ISO
10545.7

- Class 1: Walls only
 - Class 2: Residential floors w/minimal abrasive traffic
 - Class 3: Residential interiors/light commercial traffic
 - Class 4: Medium commercial applications
 - Class 5: All commercial applications/heavy traffic
- *Wear can vary greatly. please consult with a professional.*

Stain Resistance

ASTM C1378-04
UNI EN ISO
10545.14

5

- 5: Removed after 5 minutes (hot water running)
- 4: Removed by manual cleaning (weak detergent)
- 3: Removed by mechanical cleaning (strong detergent)
- 2: Removed by immersion (24 hrs in suitable solvent)
- 1: Stain not removed

Water Absorption

ASTM C-373
UNI EN ISO
10545.3

Water Absorption	Impervious	Vitreous	Semi-Vitreous	Non-Vitreous
<input checked="" type="checkbox"/> Absorbs 0-.5%	<input type="checkbox"/> Absorbs 0-.5%	<input type="checkbox"/> Absorbs .5-3%	<input type="checkbox"/> Absorbs 3-7%	<input type="checkbox"/> Absorbs 7% +
<input type="checkbox"/> Absorbs .5-3%	Impervious Interior/Exterior Frost Resistant	Vitreous Interior/Exterior Frost Resistant	Semi-Vitreous Indoor Use Only	Non-Vitreous Indoor Use Only

Breaking Strength

ASTM C648
UNI EN ISO
10545.4

PASS

Industry standard should be greater than
250 lbs
or
50 N/MM²

Facial Dimension

ASTM c499-09
UNI EN ISO
10545.02

	Standard	Tolerance	Result
flatness	±5mm	±.5%	PASS
thickness	±6mm	±.5%	PASS
straightness	±4.5mm	±.5%	PASS
squareness	±5.4mm	±.6%	PASS
sides L/W	±1.1mm ±4.5mm	±.5%	PASS

Chemical Resistance

ASTM C650
UNI EN ISO
10545.13

Allowances for:

	result
Acid	A
Bases	A
Chemicals	A

Lead Information



REQUIREMENTS
FOR COMMERCIAL
INTERIORS/NEW
CONSTRUCTION

Category	Requirement	Points
Sustainable Sites	Site selection	1 Point
	SS CREDIT 1 Heat Island Effect-non roof Material with a solar reflectant index of at least 29.	<input type="checkbox"/>
Energy & Atmosphere	EA CREDIT 4 Green Power: Products that optimize energy performance for floors and walls using thermal conductivity. BTU-FT	<input type="checkbox"/>
	Indoor Environmental Quality Low-Emitting Materials-Flooring Systems	1 Point
Indoor Environmental Quality	IEQ CREDIT 3.1-7 Green Cleaning: Reducing occupants exposure to hazardous cleaning chemicals.	<input type="checkbox"/>
	IEQ CREDIT 4.1 Low Emitting Adhesives: Products less than 65 G/L VOC	<input type="checkbox"/>
	IEQ CREDIT 4.3 Low Emitting Materials: Flooring systems.	<input type="checkbox"/>

Category	Requirement	Points
Materials & Resources	M&R CREDIT 2 Construction Waste Management: Recycling salvaged construction waste in to new reusable materials.	1 Point
	M&R CREDIT 4.1-4.2 Recycled Content: The sum of post consumer plus 1/2 of the pre consumer reps at least 10-20% of total value of materials.	2 Points
Materials & Resources	M&R CREDIT 5 Regional Materials: Materials manufactured within 500 miles of the project site.	50% <input type="checkbox"/>
	Innovation in Design	1-5 Points
Innovation in Design	ID CREDIT 1 Innovation in Design Measurable exemplary environmental performance.	10% <input type="checkbox"/>
		20% <input type="checkbox"/>

Type:
Porcelain Stoneware

Product Line:
CAPE

The marketing name for this product is property of CTS Pro. This same product may be marketed under different names.