

Aura


PORCELAIN
COLLECTION



CANCOS
TILE & STONE

BEIGE

Aura





ELEAUBE1224
ELEAUBE1224L



-12x24-
s+p

ELEAUBE2448
ELEAUBE2448L



-24x48-
s+p

ELEAUBE2448STR



-24x48 structured-
s

ELEAUBEMOS22



-2x2 mosaic-
s

ELEAUBEMOSHEX



-3" hex mosaic-
s

ELEAUBEBN324
ELEAUBEBN324L



-3x24 bullnose-
s+p

ELEAUBEMOSPAR



-parachute
mosaic- s

s = satin p = polished

GREEN

Aura





ELEAUGN1224
ELEAUGN1224L



-12x24-
s+p

ELEAUGN2448
ELEAUGN2448L




-24x48-
s+p

ELEAUGN2448STR



-24x48 structured-
s

ELEAUGNMOS22



-2x2 mosaic-
s

ELEAUGNMOSHEX



-3" hex mosaic-
s

ELEAUGNBN324
ELEAUGNBN324L



-3x24 bullnose-
s+p

s = satin p = polished


IVORY

Aura





ELEAUIV1224
ELEAUIV1224L



-12x24-
s+p

ELEAUIV2448
ELEAUIV2448L



-24x48-
s+p

ELEAUIV2448STR



-24x48 structured-
s

ELEAUIVMOS22




-2x2 mosaic-
s

ELEAUIVMOSHEX



-3" hex mosaic-
s

ELEAUIVBN324
ELEAUIVBN324L



-3x24 bullnose-
s+p

ELEAUIVMOSPAR



-parachute
mosaic- s

s = satin p = polished


WHITE

Aura





ELEAUWH1224
ELEAUWH1224L



-12x24-
s+p

ELEAUWH2448
ELEAUWH2448L




-24x48-
s+p

ELEAUWH2448STR



-24x48 structured-
s

ELEAUWHMOS22



-2x2 mosaic-
s

ELEAUWHMOSHEX



-3" hex mosaic-
s

ELEAUIVBN324
ELEAUIVBN324L



-3x24 bullnose-
s+p

ELEAUWHMOSPAR



-parachute
mosaic- s

s = satin p = polished

AURA COLLECTION

TILE

Type	Finish	Thickness	Edge	# Faces
Porcelain Glazed	Satin Polished	9mm	Rectified	*see faces below

*12x24: 30 faces, 24x48: 15 faces, 24x48 structured: 15 faces

INSTALLATION

Grout Joint	Setting	Offset %	Shade Variation
1/16"			 V2 (Slight)

PERFORMANCE

	Test Method	Result
Water Absorption	ASTM C373	<0.5%
Breaking Strength	ASTM C648	>50 N/mm ²
Scratch Hardness	MOHS	6
Wear Resistance	ANSI A137.1	Class 4
Slip Resistance	ASTM C1028	R9, Class A
Chemical Resistance	ASTM C650	Resistant
Stain Resistance	ASTM C1378	5
Thermal Shock Resistance	ASTM C484	Resistant
Freezing Resistance	ASTM C1026	Resistant

APPLICATIONS

	Suitable	DCOF*
Dry & Level - Interior Floor	✓	N/A
Wet & Level - Interior Floor	✓	≥0.42*
Shower Floors	✓	≥0.42*
Exterior Floors (including patios, pool decking and other wet areas with minimal footwear)		
Ramps and Inclines		
Walls & Backsplashes	✓	
Countertops		
Pool Linings		
Residential	✓	
Light Commercial	✓	
Heavy Commercial		

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3
 *A DCOF rating does not apply to polished finishes

NOTES

- Variations occur in all fired ceramic and natural tile products.
- Random visual variation enhances the natural beauty of this product.
- For optimal results:
 - Select tile from multiple cartons.
 - Plan shading and graphic arrangement prior to installation.
- Tile/trim supplied for a particular installation may not match samples exactly.
- Final confirmation of actual tiles and trim should be made prior to installation.
- Products are manufactured in accordance with ANSI A137.1 standards.
- Special care should be taken when grouting with dark pigmented colors.
- Use of a latex-modified thin-set is recommended for installation.

LEED CERTIFICATIONS 4.1

	Points	
New Building Design + Construction		
Sustainable Sites	1 pt	A test may need to be conducted if required, but lighter colors should have a sufficiently high SRI
Energy and Atmosphere	1 pt	Conductivity: 1.0-1.3 W/mK
Materials and Resources	5 pts	Recycled Content + EPD + HPD + REACH + Sustainability Report
Indoor Environmental Quality	1-3 pts	GREENGUARD Gold Certified